





 $\hat{O}[|[``| \bullet \acute{A} \Delta \acute{A} j ~ \tilde{a} @ \circ \acute{A} @] \} \acute{A} d ^{A} j ~ \acute{A} j$

SPECIFICATIONS

FEATURES

îÁ&^|ÁÕ¦[ĭ]ÁŠcåÁ¢Á,,,Ècd^^cĕ¦}ãč¦^È8[È;

Code	S114R-900WFER - Stainless Steel Bollard	• 304 stainless steel electropolished
	- Hot Dip Galv Socket	 Hot dip galvanised inground socket for
		longlife
Material	304 Stainless Steel (Removable Bollard)	Removable bollard with optional lockable
Height	900mm Above Ground	cover (Padlock not supplied) • Welded Flat top
	475mm into Socket (1375mm Overall)	 Wheel friendly flush closing inground socket cover when bollard is removed
Diameter	Ø114.3 x 4.5 - Wall Tube	
Weight	22 Kg (Removable Bollard)	
Mounting	Socket Cast into Concrete 475mm Deep	
_	Bollard Lug Padlocked to cover socket	
	l	

 Bollards are not supplied with installation instructions, install fastenings or footing details. These are to be specified and determined by the installing contractor for the specific requirements of each site.