





 $\hat{O}[\ \|[\ ``\ | \bullet \not A \not A \not a]\ \tilde{a}\ @\bullet \bullet \not A\ @\ _\]\ A \not a \not a \partial B \partial \partial \partial \mathring{a}\ \tilde{a}\ (A \not a)\ A \not a \not a A \not a - A \not a \not a A \partial \partial \mathring{a}\ A \cap A \not a \partial \mathring{a}\ \hat{a}\ \hat{a$

FEATURES

Code	BOL0191 - MS Body, Galv Inground Socket	• 304 or 316 stainless steel electropolished
	BOL0192 - Powdercoated MS Body, Galv Socket	 Mild steel hot dip galv & powdercoated
	BOL0194 - 304 S/S Body, Galv Inground Socket	 Hot dip galvanised inground socket for
	BOL0195 - 316 S/S Body, Galv Inground Socket	long life
Material	304/316 Stainless Steel or Mild Steel Galvanised	 Removable bollard with optional lockable cover (Padlock not supplied)
Height	900mm Above Ground	Optional Welded Flange at ground levelWelded Flat top
	285mm Below Ground (1185mm Overall)	 Suitable for architectural applications
Diameter	Ø114.3 x 1.5 - Stainless Steel	
	Ø114.3 x 2 - Mild Steel	
Weight	22 Kg (Removable Bollard)	

SPECIFICATIONS

Socket Cast into Concrete 285mm Deep

Mounting

• Bollards are not supplied with installation instructions, install fastenings or footing details. These are to be specified and determined by the installing contractor for the specific requirements of each site.