









 $\hat{O}[|[\text{``}|\bullet \text{AbA}] \tilde{a} @ \bullet \text{A} @]_{\text{\downarrow}} \hat{A} \text{ab}^{\wedge} \hat{A} \text{ \downarrow} \hat{a} \tilde{a} \text{Bases} \tilde{a} \text{\uparrow}^{\wedge} \hat{A}_{\text{\downarrow}})^{\hat{A}} \hat{A} \text{ab} \hat{a} \hat{A} \text{ \downarrow} \hat{A} \text{ab}^{\hat{A}} \hat{A} \text{ \downarrow} \hat{A}$

SPECIFICATIONS

CodeRVIAR-880CSBPF2Material316 Grade Stainless SteelHeight880mm Above Ground300mm In-Ground (1180mm Overall)DiameterØ114.3 x 3.05mm Wall TubeBase PlateØ170 x 5mm ThickWeight12 KgMountingCast into Concrete 300mm Deep

FEATURES

- Welded and dressed head with rebated collar
 - Welded flange at ground level
 - Bead blasted finish
 - Welded bar for fixing into concrete
 - Suitable for architectural applications

• Bollards are not supplied with installation instructions, install fastenings or footing details. These are to be specified and determined by the installing contractor for the specific requirements of each site.